

Disclaimer

THIS SPECIFICATION IS LICENSED AND PROVIDED BY LOGITECH "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL LOGITECH OR ANY OF ITS AFFILIATED COMPANIES BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SPECIFICATION, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

[0x4301] Solar Kbd Dashboard DRAFT SPEC

```
max_num_of_reports,report_period = [0]SetLightMeasure(max_num_of_reports,
report_period)
LED_ID = [1]SetLED(LED_ID)
```

Application Specific Event

Broadcast Event

```
BattStatus = [0]BatteryBroadcastEvent
BattLightStatus = [1]BattLightMeasureBroadcastEvent
BattLightStatus = [2]CheckLightButtonBroadcastEvent
```

FUNCTIONS

SetLightMeasure

Summary

Gives the current light measure in lux (min 0 = 0 lux, max 511 = 511 lux)

Parameters

max_num_of_reports [8bits] Maximum number of BattLightMeasureEvents that will be sent after function call (0 = cancel event reporting)
report_period [8bits] Minimum time (1s units) between two consecutive BattLightMeasureEvents (0 = cancel event reporting)

Errors

None

Remarks

max_num_of_reports counter must be reset when exiting disconnected mode.
example:

```
8 41 03 06 0X10 03 06 0F 05 02 00 SetLightMeasure
5 1
8 43 03 06 0R11 03 06 0F 05 02 00 00 00 00 00 00 00 00 00 00 00 00
8 8
8 44 3 SetLightMeasure response
7 2 [ num_of_reports: 5, period: 2 seconds]
```

Request

0	1	2
max_num_of_reports	report_period	0

Response

0	1	2
max_num_of_reports	report_period	0

SetLED

Summary

Light the selected LED for the duration (hard-coded in FW)

Parameters

LED_ID [8bits] Target LED (0=LEDS_OFF, 1=RED, 2=ORANGE, 3=GREEN)

Returns

[void]

Errors

none

Remarks

SetLED is supposed to be used only to override the FW CheckLight LED display. FW will wait 250ms before displaying CheckLight status on LEDs, to let host SW enough time to react to the CheckLightButtonBroadcastEvent. If SW sends the SetLED before the 250ms timeout expires, the FW does not display CheckLight status on LEDs at all, but if timeout expires, FW displays its own CheckLight status.

Request

0	1	2
LED_ID	0	0

Response

0	1	2
LED_ID	0	0

EVENTS

BatteryBroadcastEvent

Reports **battery capacity** to host SW **spontaneously each 90s** when keyboard is being used A report is also sent at power-up and when exiting disconnected mode.

LightLevelMeasure bytes are set to 0.

```

13 07
2 12:22: 83 03 06 Notif 0 R (91000)11 03 06 00 60 00 00 06 72 47 4F 4F 44 00 00 00 00 00 00
46 7
65
71
13 83
5 8 Broadcast Event[BattLightBroadcastEvent] received [BatteryLevel:
1 96%, LightLevel: 0, BattADC: 2.67793237653V]
K750 received after 71.8300018311 s

```

BattLightMeasureEvent

Reports **battery and light level** to host SW according to parameters provided by SetLightMeasure function

```

10 07
8 9 03 06 Notif 1 R (3000)11 03 06 10 60 01 3F 06 72 47 4F 4F 44 00 00 00 00 00 00
65 9 3
71 9 3
11 08
1 0 Broadcast Event[BattLightMeasureBroadcastEvent] received
1 [BatteryLevel: 96%, LightLevel: 319, BattADC: 2.67793237653V]
K750 received after 0.0 s

```

CheckLightButtonBroadcastEvent

Flag that CheckLight button has been pressed and report also **battery and light level** to SW

```

13 00
2 6 03 06 Notif 2 R (91000)11 03 06 20 60 00 00 06 72 47 4F 4F 44 00 00 00 00 00 00
65 6 3
71 6 3
13 00
5 7 Broadcast Event[CheckLightButtonBroadcastEvent] received
1 [BatteryLevel: 96%, LightLevel: 0, BattADC: 2.67793237653V]
K750 received after 0.0 s

```

Report

BatteryLevel [8bits] The remaining battery capacity as defined in [Notes Link](#),

LightLevelMeasure [16bits] Gives the current light measure in lux

Remarks

See BattLightMeasureEvent remarks

NOTE: When CheckLight button is pressed, the HID code page 0x0C, usage 0x01F0 is also sent (dummy keystroke, sent for FW internal reasons)

Report

	0	1	2
BatteryLevel	new	LightLevelMeasure MSB	LightLevelMeasure LSB